

# S9 dyna

100-250 HP

∅ max. 9 cm [3.5 inch]

## Heavy duty flail mulcher with innovative reversible linkage

The S9 series machines mulch grass, vegetation and prunings up to 9 cm [3.5"] in diameter. The adjustable rear hood allows you to alter the degree of mulching.

The **S9 dyna** is characterized by an innovative, pyramid-shaped 3-point linkage, suitable for front and rear attachment. The top link connection provides high stability and is easily reversed to allow front or rear mount to be achieved without heavy lifting.

## Standard version and characteristics

- > Mulches grass and brush up to 9 cm [3.5"]∅
- > Working speed 3-10 km/h
- > 3 point linkage cat. 2 reversible
- > Linear hydraulic side shift
- > 1000 rpm gearbox with freewheel and through shaft
- > Belt transmission
- > Adjustable rear hood with rubber protection
- > Front protection with chains
- > Support roller 193 mm ∅
- > Rotor with SMO flails

## Optional configuration and accessories

- > 540 rpm gearbox
- > Gearbox with automatic inverter and double freewheel
- > Belt cover on the right (working left)
- > Additional front rubber flap
- > Roller scraper
- > Rubber wheels instead of roller



[www.youtube.com/seppimulcher](https://www.youtube.com/seppimulcher)

## Tools



Flails  
SMO

Specifications · S9 dyna			Nominal tractor power 100-250 HP				
		cm [inch]	200 [79]	225 [89]	250 [98]	275 [108]	300 [118]
Working width		cm [inch]	200 [79]	225 [89]	250 [98]	275 [108]	300 [118]
Side shift from middle of tractor	max to the left	L R cm [inch]	133 67 [52 26]	153 72 [60 28]	133 117 [52 46]	151 124 [59 26]	151 149 [52 49]
	max to the right	L R cm [inch]	66 134 [26 53]	85 140 [33 55]	66 184 [26 72]	84 191 [33 75]	84 216 [33 85]
Overall width		cm [inch]	215 [85]	240 [95]	265 [100]	290 [114]	315 [124]
Depth		cm [inch]	127 [50]	127 [50]	127 [50]	127 [50]	127 [50]
Height		cm [inch]	130 [51]	130 [51]	130 [51]	130 [51]	130 [51]
Weight · base value		kg	930 [2,050]	1.010 [2,227]	1.100 [2,425]	1.190 [2,624]	1.280 [2,822]
Belts	Anzahl		5	5	5	5	5
Flails	Anzahl		21	24	27	27	30

### S9 dyna · features

Strong and robust casing made of high-tensile steel, with replaceable wear plates.



**Innovative, pyramid-shaped 3-point linkage with high stability, suitable for front and rear attachment**  
**FR**  
FRONT & REAR

**Gearbox for front- and rear attachment**

**Hydraulic side shift: linear up to 68 cm [27"]**

**Adjustable hood to set the degree of mulching**  
**M-FLAP**

**Strong roller with double tapered bearing unit for a long life, the large diameter improves mulching on uneven ground.**

**Due to the close position of the roller to the rotor, the rotating flails clean the roller, and the cut material is evenly distributed over the top.**

**Rotor with SMW flails**  
 Low power consumption at maximum throughput with helix rotor technology  
**HELIX ROTOR**

**Replaceable tempered counter cutters inside the casing provide a perfect result when mulching.**  
**2 COUNTER CUTTERS**